PowerUltra

The Salient PowerUltra is a 2U rack-mount NVR designed to handle complex video surveillance requirements utilizing highly scalable memory, I/O capabilities and extended storage capacity making it ideally suited for intensive digital video processing. Tailor your enterprise video requirements with the PowerUltra's offering of high performance CPU power, 16GB UDIMM memory, hot-plug swappable hard drives and dual hot-plug redundant power supplies.

The lower overall system-level power draw is the result of breakthrough system design. The PowerUltra NVR maximizes performance per watt through a combination of power and cooling, and energy efficient technologies and tools.

Features

- Record, live view, playback, archive video
- Hybrid NVR for analog (max 64 channels) and IP cameras
- Rack mount 2U form factor
- Front access with locking bezel for hotswap

Tech Specs at a Glance			
System Performance Class: Enterprise Level			
CPU	Dual Intel Xeon Dual E5 - 2620		
Memory	16GB UDIMM, 1333 MT/S		
Network	Quad 10/100/1000 NICS		
Storage	12TB – 40TB RAID5		
Windows OS	Windows Server 2008 Std R2		



PowerUltra

Technical Specifications

Item	Description	
Processor	Dual Intel Xeon E5-2620	
Operating System	Windows Server 2008 Std R2	
Memory	16GB (8 x 2GB) UDIMM. 1333Mhz	
Network • Hybrid Capable • IP Camera Support	Quad 10/100/1000 Mbps NIC YES, up to 64 direct connect analog cameras YES	
Hard Drive (OS)	146GB RAID1 mirror using 15,000 RMP SAS Enterprise class drives	
Hard Drive (Video Storage)	12TB, 16TB, 18TB, 24TB, 30TB, 40TB (usable storage) hot-swap RAID5 configurations using 7200 RPM SATA Enterprise class drives.	
Raid Controller	Perc H710 Mini	
Graphics Adapter	Matrox G200eR video Controller	
Video Display Ports	1x VGA port	
USB Ports	1 Front USB 2.0; 2 Rear USB 2.0	
Other Ports	1 Serial	
Optical Drive	External USB attached DVD-RW (optional accessory available)	
Accessories	None	
Options	iDRAC Enterprise software PN: CV-iDRAC-ENT-Ultra	

Chassis Features

Form Factor: 2U Rack Mountable		Operating Environment	
Dimensions with Rails	3.44" H x 18.98" W x 29.75"D	System Operating Environment	50°F - 95°F (10°C - 35°C)
Dimensions without Rails	3.44" H x 17.08" W x 29.75"D	Power Supply	Dual, Hot-plug, Redundant, 750W AC power supply
Weight Relative	71.51 lbs / 32.4 kg	Humidity	10 ~ 80%

HOW TO ORDER

Purchase: orders@salientsys.com Pricing: sales@salientsys.com

For more information visit www.salientsys.com

Company and product names mentioned are registered trademarks of their respective owners. Salient Systems reserves the right to change specifications without prior notice.

Copyright Salient Systems. 02/2014

Follow Us On twitter.com/Salientsys

