

Continental Access: Introducing our full line of easy to use exit switches and REX motion sensors

Access exit switches and sensors

Continental Access offers a wide range of exit switches and REX motion sensors. All sensors and switches have easy installation with Continental Access controllers. Switches in a variety of options including single pole, double-pole-double-throw and narrow styles are available for tight locations and door frames. Choose from exterior and vandal resistant switch options for harsh environments or REX motion sensors for automated exit convenience. Trust Continental Access to offer excellent value, easy to use hardware and quality accessories to accompany our feature rich software.

Single pole illuminated switches

CA-SIS2

- SPDT illuminated
- 12/24 volt AC/DC replaceable bulb - 25,000 hr.)
- 2" square pushbutton switch
- Labeled "PUSH TO EXIT"
- Mounted on single gang wall plate
- Rated 10 amp @ 35VDC or 120VAC



Single pole mushroom button switches

CA-SBS1

- 1.5" red mushroom button switch
- One N/O and one N/C contact
- Mounted on single gang
- Labeled "EXIT"
- Rated 10 amp @ 35VDC or 120VAC



CA-SBS27N

- 1.5" green mushroom button switch
- One N/O and one N/C contact
- Screw terminals
- Mounted on 1.75" narrow wall plate
- Labeled "PUSH TO EXIT"
- Rated 10 amp @ 35VDC or 120VAC



Single pole pneumatic time delay switches

CA-SP14

- Pneumatic time delay switch
- Requires no external power
- One N/O and one N/C contact
- Mounted on single gang wall plate
- Labeled "PUSH TO EXIT"
- Rated 10 amp @ 120/240 Volts



CA-SP14N

- Pneumatic time delay switch
- Requires no external power
- One N/O and one N/C contact
- Mounted on 1.75" narrow wall plate
- Labeled "PUSH TO EXIT"
- Rated 10 amp @ 120/240 Volts



Single pole throw time delay switches

CA-ST2

- Electronic time delay switch
- SPDT illuminated
- 1 momentary SPDT
- 30 second built-in timer
- 2amp @ 12 - 28 VDC



Double pole double throw illuminated switches

CA-SID2

- DPDT illuminated
- 12/24 volt AC/DC
- Replaceable bulb - 25,000 hr)
- 2" square pushbutton switch
- Labeled "PUSH TO EXIT"
- Mounted on single gang wall plate
- Rated 10 amp @ 35VDC or 120VAC



CA-SID9N

- DPDT illuminated
- 12/24 volt AC/DC high brightness led
- .675" x .875" pushbutton switch
- Labeled "PUSH TO EXIT"
- Mounted on 1.75" narrow wall plate
- Rated 3 amp @ 35VDC or 120VAC



CA-SID7

- DPDT illuminated
- 12/24 volt AC/DC high brightness led
- .675" x .875" pushbutton switch
- Labeled "PUSH TO EXIT"
- Mounted on single gang wall plate
- Rated 3 amp @ 35VDC or 120VAC



Double pole double throw vandal resistant switches

CA-SV13N

- DPDT vandal resistant
- .750" diameter pushbutton
- Mounted on 1.75" narrow wall plate
- Labeled "PUSH TO EXIT"
- Rated 4 amp @ 25VDC or 125VAC
- IP65 rated



CA-SV12

- DPDT vandal resistant
- .750" diameter pushbutton
- Mounted on single gang wall plate
- Labeled "PUSH TO EXIT"
- Rated 4 amp @ 25VDC or 125VAC
- IP65 rated



CA-SV111

- DPDT vandal resistant
- Single gang push plate
- Labeled PUSH TO EXIT
- Rated 4 amp @ 28VDC



Request-to-exit (REX) PIRs

CA-PS520-W

- Passive infrared sensor, adjustable sensitivity
- 12 or 24 VAC or VDC
- Hold time 0.25 to 60sec
- Single/double door pattern
- Adjustable 35° vertical wall mount
- Adjustable 20° vertical overhead mount
- Off white housing



CA-PS520-S

- Passive infrared sensor, adjustable sensitivity
- 12 or 24 VAC or VDC
- Hold time 0.25 to 60sec
- Single/double door pattern
- Adjustable 35° vertical wall mount
- Adjustable 20° vertical overhead mount
- Silver housing



Single pole: Illuminated, mushroom, time delay

Double pole, double throw exit switches & REX PIRs

Exit switches: Ordering guide

DOUBLE POLE

SINGLE POLE

	Part No.	Narrow Stile	Illuminated	Electric Time Delay	Pneumatic Time Delay	Labeled	Voltage	Push Button Switch Size	Vandal Resistant
	CA-SID2		●			Push To Exit	10amp @ 35VDC or 120VAC	2"	
	CA-SID7		●			Push To Exit	3amp @ 35VDC or 120VAC	.675" x .875"	
	CA-SID9N	●	●			Push To Exit	3amp @ 35VDC or 120VAC	.675" x .875"	
	CA-SV12					Push To Exit	4 amp @ 25VDC or 125VAC	.750" dia..	●
	CA-SV13N	●				Push To Exit	4amp @ 25VDC or 125VAC	.750" dia.	●
	CA-SV111					Push To Exit	4amp @ 28VDC		●
	CA-ST2		●	●		Push To Exit	2amp @ 12-28 VDC	2"	
	CA-SIS2		●			Push To Exit	10 amp @ 35VDC or 120VAC	2"	
	CA-SBS1					Exit	10 amp @ 35VDC or 120VAC	1.5" dia.	
	CA-SBS27N					Push To Exit	10 amp @ 35VDC or 120VAC	1.5" dia.	
	CA-SP14				●	Push To Exit	10 amp @ 120/240 Volts	1.5" dia.	
	CA-SP14N	●			●	Push To Exit	10 amp @ 120/240 Volts	1.5" dia.	

For more information, please contact your local sales representative or contact Continental Access directly at (631) 842-9135.



Continental Instruments, A Napco Security Group Company • 355 Bayview Ave., Amityville, NY 11701
Phone (631) 842-9400 • Fax (631) 842-9135 • www.cicaccess.com GSA GS-07F-00039H
CardAccess® and CI SQL 3000™ are trademarks of Continental/NAPCO, 2007 A580

Continental Access: Reliable exit switches and sensors

- Easy to use
- Excellent value
- Full line of single pole and double pole models for every access application

