Face Mode

Fingerprint Mode

Your Face is your Key
Access Control or
Time Clock Version Available

Users of the EntryGuard™ Face & Fingerprint Professional Station (PRO) can clock in/out at work or access the facilities.

Three Factor ID is Available: The design permits the PRO to operate in one, two or three factor mode. The PRO has five ID methods which affords 19 ID combinations.   The ID methods are: face, fingerprint, PIN, password or card reader. The ID methods can be presented in any order.

The FaceKey™ Face & Fingerprint Professional Station can function as a standalone device or multiple units can be connected over a network. Each unit is TCP/IP addressable and has a unique MAC address visible on the internet.

The FKFP-AC-PRO when used for access control is a full featured access control device, see "Benefits and Features". The EntryGuard™ FKFP PRO unit is available with a RFID card reader (Generic or Mifare). The PRO when used as a time clock has the same features except the unit does not unlock doors.

 Software: The FaceKey™ Management Software automatically synchronizes all FaceKey EntryGuard™ devices with the network and manages the face and fingerprint templates. If the network fails, the units will continue to operate and collect data which will be uploaded when communication with the network is reestablished. The EntryGuard™ Time and Attendance Management Software provides business rules and reports for time and attendance.

Scalable: The FaceKey™ Management Software database supports an unlimited number of devices and users. Each Standard Face & Fingerprint Station can accommodates up to 2,000 fingerprint templates and 500 1:many and 3,000 1:1 face templates. Call FaceKey for units with additional templates.

FaceKey™ Corporation
900 NE Loop 410, Suite D401
San Antonio, TX 78209
210-826-8811
www.facekey.com
Email: info@facekey.com

Standard FKFP-AC models and part nos.   Contact FaceKey for special order products.

Description	Model #	Part #
Standard	FKFP-AC-PRO	8033127
Generic Card	FKFP-AC-PRO+EM	8033129

Benefits and Features:
- Easy installation
- Connects directly to local area network
- Red and green status indicators
- Six(6) user defined function key
- 3" touch screen (TFT) display
- Optical fingerprint reader
- Auto correction contrast & brightness
- Face recognition
- Fingerprint recognition
- Virtual keyboard and keypad
- Three factor ID: (19 ID combinations)
  - Face+fingerprint+card (example)
- Professional access control features
  - 50 Time zones
  - 10 Unlock combinations
  - 5 Groups
  - Anti-pass back
  - Tamper switch
  - Alarm output
  - Door sensor input
  - Exit request input
  - Door bell button
- Holiday schedule
- Egress function (schedule door to open/lock)
- Acknowledgment of acceptance: LED indicator, display indication and voice reply
- SMS (Short Message System)

Technical Specifications:
- Identification (Fingerprint)
  - Time: <=0.8s
  - FAR: <=0.0001%
  - FRR: <=1%
- Identification (Face)
  - Time   <=3s
- Transaction Capacity:
  - Event Log   100,000 events
  - Faces   "see Scalable"
  - Fingerprints   "see Scalable"
- Connectivity: TCP/IP, RS232, RS485
- Wiegand output (26 or 34 bit standard)
- USB ports: 1
- Voltage input: 12 VDC (supply included)
- Indoor use only
- Temperature range: 32°◦ 113°F (0°-45°C)