PowerPlus

The Salient PowerPlus is a 2U rack-mount NVR offering an excellent balance between processing power, storage capacity, redundancy for high performance and a flexible platform for video surveillance applications. The PowerPlus is optimized for performance with extensive memory and storage. It utilizes enhanced I/O capabilities with Salient's CompleteView VMS and is engineered for the rigors of continuous duty operation. Using best in class components, the PowerPlus provides the reliability and processing power required by mission critical video surveillance architectures.

Lower overall system-level power draw is the result of breakthrough system design. The PowerPlus NVR maximizes performance per watt through a combination of power and cooling, and energy efficient technologies and tools.

Features

- Record, live view, playback, archive video
- Hybrid NVR for analog (max 64 channels) and IP cameras
- Rack mount 2U form factor
- Front access with locking bezel for hotswap

Tech Specs at a Glance			
System Performance Class: Enterprise Level			
CPU	Intel Xeon Dual E5 - 2407		
Memory	12GB UDIMM		
Network	Dual 10/100/1000 NICS		
Storage	4TB – 16TB RAID5		
Windows OS	Windows Server 2008 Std R2		



PowerPlus

Technical Specifications

Item	Description		
Processor	Dual Intel Xeon E5-2407		
Operating System	Windows Server 2008 Std R2		
Memory	12GB (6x2GB) UDIMM, 1333Mhz		
Network • Hybrid Capable • IP Camera Support	Dual 10/100/1000 Mbps NICS YES, up to 64 directly connected analog cameras YES		
Hard Drive (OS)	500GB RAID1 mirror using 7.2K RPM SATA Enterprise class drives		
Hard Drive (Video Storage)	4TB, 8TB, 12TB and 16TB (usable storage) hot-swap RAID5 configurations using 7200 RPM SATA Enterprise class drives.		
Raid Controller	Perc H710 Mini		
Graphics Adapter	Matrox G200eR video controller		
Video Display Ports	1 VGA		
USB Ports	2 Front USB 2.0; 2 Rear USB 2.0		
Other Ports	1 Serial		
Optical Drive	External USB attached DVD-RW (optional accessory)		
Accessories	None		
Options	iDRAC Enterprise kit PN: CV-iDRAC-ENT-Plus		

Chassis Features

Form Factor: 2U Rack Mountable		Operating Environment	
Dimensions with Rails	3.44" H x 18.98" W x 29.75"D	System Operating Environment	50°F - 95°F (10°C - 35°C)
Dimensions without Rails	3.44" H x 17.08" W x 29.75" D	Power Supply	Dual, Hot-plug, Redundant, 750W AC power supply
Weight Relative	71.51lbs/ 32.4 kg	Humidity	10 ~ 80%

HOW TO ORDER

Purchase: orders@salientsys.com Pricing: sales@salientsys.com

For more information visit www.salientsys.com

Company and product names mentioned are registered trademarks of their respective owners. Salient Systems reserves the right to change specifications without prior notice.

Copyright Salient Systems. 02/2014

Follow Us On **twitter.com/Salientsys**

