

Date/Doc revision: 19-Apr-2024

Project Name: Panic Pendant



A907LF

TECHNICAL SPECIFICATIONS

- **Model:** Ppanic
- **Tamper:** N/A
- **LED:** x1
- **Button:** x1
- **Wired:** N/A
- **Case Material:** PC+ABS
- **Screws:** x4 PB1.7 x 5mm
- **Color:** White
- **Mounting:** Wristband, Belt clip
- **Battery:** CR2032 3.0V (225mAh) x1
- **Battery Life:** \approx 7 years @ 30 triggers per day
- **Standby Current:** 0.9 μ A
- **Active Current:** 2.4 mA
- **Operating Temperature:** 32° to 120.2°F (0° to 49°C)
- **Relative Humidity (Storage):** 80% Max. non-condensing
- **Weather Proofing:** IPX7
- **Regulatory:** FCC, ETL (Chemical Certification Only), RCM



CONNECTIVITY

- **Transmitter Frequency:** 433MHz
- **Wireless Signal Range:** up to 492 ft.*, open air, with Security Panel**
- **Modulation:** OOK
- **Encryption:** Yes, 1-way
- **Frequency Hopping:** N/A
- **Supervision:** N/A

DIMENSIONS

- **Height:** 1.65 in.
- **Width:** 1.45 in.
- **Depth:** 0.43 in.

FEATURES

- **Actions:** Medical, Police, Mode Set at The XP02 Panel

* The front of the Sensor is facing the panel LCD. The panel is installed at a height of 4.92 ft. The Sensor is installed at a height of 4.59 to 4.92 ft.

** The location of the Sensor can have a significant effect on range. In open/unobstructed situations, the transmitter range may be greater. In adverse wireless conditions, you may encounter a decrease in range.